

IN THE CLAIMS:

Amendments to the Claims:

Please amend claims 1, 2, 4 and 6-8 as shown below.

Listing of Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (currently amended) An image display device comprising:
a face substrate which ~~forms~~has anodes and phosphors formed on an inner surface thereof:

a back substrate₁ which ~~forms~~has: a plurality of cathode lines which extend in one direction and are arranged in parallel in another direction which intersects one direction, which cathode lines include electron sources₁; control electrodes which are arranged to face the cathode lines in a non-contact manner and include a plurality of electron passing holes which allow electrons emitted from the electron sources to pass therethrough to an inner surface side of the face substrate in regions which respectively face the electron sources and control an emission quantity of electrons emitted from the electron sources₁; and acceleration electrodes which face the control electrodes in a non-contact manner, include a plurality of electron passing holes which allow the electrons which pass through the electron passing holes formed in the control electrodes to pass therethrough in regions which respectively face the respective electron passing holes formed in the control electrodes and

which accelerate the electrons which pass through the electron passing holes on an inner surface thereof;~~;~~ and said back substrate being disposed to face the face substrate with a given distance therebetween; and

a frame body which is inserted between the face substrate and the back substrate while surrounding a display region ~~and holds~~ so as to maintain a given distance between the face substrate and the back substrate;~~;~~ wherein

assuming a distance between the electron sources and the control electrodes as L_{kg} , a distance between the control electrodes and the acceleration electrodes as L_{12} , a thickness of the electron passing holes formed in the control electrodes as T_{gl} and a short diameter of the electron passing holes formed in the control electrodes as FGI , the acceleration electrodes satisfy the relationship $(L_{kg} + T_{gl} + L_{12}/2)/FGI \geq 0.25$;~~;~~

assuming a thickness of the electron passing holes formed in the acceleration electrodes as T_{g2} and a short diameter of the electron passing holes of the acceleration electrodes as $FG2$, the acceleration electrodes satisfy the relationship $T_{g2min} \leq T_{g2} \leq T_{g2max}$ and the relationship $T_{g2min} = 2.98FG2 - 0.04$;~~;~~

assuming $FG2 < 0.109$, the acceleration electrodes satisfy the relationship $T_{g2max} = 0.02/(0.115 - FG2) - 0.06$;~~;~~ and

assuming $FG2 \geq 0.109$, the acceleration electrodes satisfy the relationship $T_{g2max} = 0.03/(FG2 - 0.1) + 0.045$.

2. (currently amended) An image display device comprising:

a face substrate which ~~forms~~ has anodes and phosphors formed on an inner

surface thereof:

a back substrate₁ which ~~forms~~ has a plurality of cathode lines which extend in one direction and are arranged in parallel in another direction which intersects one direction₁ ~~and~~ which cathode lines include electron sources₁; control electrodes which are arranged to face the cathode lines in a non-contact manner₁ and include a plurality of electron passing holes which allow electrons emitted from the electron sources to pass therethrough to an inner surface side of the face substrate in regions which respectively face the electron sources and control an emission quantity of electrons emitted from the electron sources₁; and acceleration electrodes which face the control electrodes in a non-contact manner, include a plurality of electron passing holes which allow the electrons which pass through the electron passing holes formed in the control electrodes to pass therethrough in regions which respectively face the respective electron passing holes formed in the control electrodes, the electron passing holes being formed while having an N-stage structure in which an open hole diameter thereof is gradually increased in the direction toward the face substrate, and which accelerate the electrons which pass through the electron passing holes toward the inner surface side of the face substrate on an inner surface thereof₁ ~~and~~ and back substrate being disposed to face the face substrate with a given distance therebetween; and

a frame body which is inserted between the face substrate and the back substrate while surrounding a display region ~~and holds~~ so as to maintain a given distance between the face substrate and the back substrate₁; wherein

assuming a distance between the electron sources and the control electrodes

as L_{kg} , a distance between the control electrodes and the acceleration electrodes as L_{12} , a thickness of the electron passing holes formed in the control electrodes as T_{gl} and a short diameter of the electron passing holes formed in the control electrodes as F_{gl} , the acceleration electrodes satisfy the relationship $(L_{kg} + T_{gl} + L_{12}/2)/F_{gl} \geq 0.25$;

assuming a thickness of a first-stage open hole of the electron passing hole of the acceleration electrode as T_{g2-1} , a thickness of open holes ranging from the first-stage open hole to a Nth-stage open hole of the electron passing hole of the acceleration electrode as T_{g2-N} , a short diameter of the first-stage open hole of the electron passing hole of the acceleration electrode as F_{g2-1} , a short diameter of the Nth-stage open hole of the electron passing hole of the acceleration electrode as F_{g2-N} , a minimum value of a thickness of open holes ranging from the first-stage open hole to the Nth-stage open hole as $T_{g2min-N}$, and a maximum value of a thickness of open holes ranging from the first-stage open hole to the Nth-stage open hole as $T_{g2max-N}$, the acceleration electrodes satisfy the relationship $F_{g2-1} < F_{g2-2} < \dots < F_{g2-N}$;

wherein with respect to at least one T_{g2-N} , the relationship $T_{g2-N} \geq T_{g2min-N}$ is satisfied, and with respect to all T_{g2-N} , the relationship $T_{g2-N} \leq T_{g2max-N}$ is satisfied.

3. (original) An image display device according to claim 1, wherein the electron sources are made of carbon nanotubes.

4. (currently amended) An image display device comprising:

a face substrate which ~~forms~~ has anodes and phosphors formed on an inner surface thereof:

a back substrate₁ which ~~forms~~ has: cathodes which form electron sources on a display region₁; control electrodes which are arranged to face the cathodes in a non-contact manner, and include a plurality of electron passing holes which allow electrons emitted from the electron sources to pass therethrough to an inner surface side of the face substrate in regions which respectively face the electron sources and control an emission quantity of electrons emitted from the electron sources₁; and acceleration electrodes which face the control electrodes in a non-contact manner, include a plurality of electron passing holes which allow the electrons which pass through the electron passing holes formed in the control electrodes in regions which respectively face the respective electron passing holes formed in the control electrodes and which accelerate the electrons which pass through the electron passing holes toward the inner surface side of the face substrate on an inner surface thereof, ~~and~~; said back substrate being disposed to face the face substrate with a given distance therebetween; and

a frame body which is inserted between the face substrate and the back substrate while surrounding a display region ~~and holds~~ so as to maintain a given distance between the face substrate and the back substrate₁; wherein

assuming a distance between the electron sources and the control electrodes as L_{k1} , a distance between the control electrodes and the acceleration electrodes as L_{12} , a thickness of the electron passing holes formed in the control electrodes as

Tg1 and a short diameter of the electron passing holes formed in the control electrodes as FGI, the acceleration electrodes satisfy the relationship $(Lkg + Tg1 + L12/2)/FGI \geq 0.25$;

assuming a thickness of the electron passing holes formed in the control electrodes as Tg2 and a short diameter of the electron passing holes of the acceleration electrodes as FG2, the acceleration electrodes satisfy the relationship $Tg2min \leq Tg2 \leq Tg2max$ and the relationship $Tg2min = 2.98FG2 - 0.04$;

assuming $FG2 < 0.109$, the acceleration electrodes satisfy the relationship $Tg2max = 0.02/(0.115 - FG2) - 0.06$; and

assuming $FG2 \geq 0.109$, the acceleration electrodes satisfy the relationship $Tg2max = 0.03/(FG2 - 0.1) + 0.045$; and

matrix driving is performed using the control electrodes and the acceleration electrodes.

5. (original) An image display device according to claim 4, wherein the electron sources are made of carbon nanotubes.

6. (currently amended) An image display device according to claim 1, wherein the control electrodes and the acceleration electrodes adopt ~~the~~ a laminated film electrode structure in which the control electrodes are formed of a first conductive metal film and the acceleration electrodes are formed of a second conductive metal film.

7. (currently amended) An image display device according to claim 1, wherein the control electrodes and the acceleration electrodes adopt ~~the~~ a laminated electrode structure in which the control electrodes are formed on the cathode line side of the insulation substrate using a first conductive metal film and the acceleration electrodes are formed on the anode side of the insulation substrate using a second conductive metal film.

8. (currently amended) An image display device according to claim 1, wherein the control electrodes and the acceleration electrodes adopt ~~the~~ a laminated electrode structure in which the control electrodes are formed on the cathode line side of the insulation substrate using a strip-like electrode element and the acceleration electrodes are formed on the anode side of the insulation substrate using a conductive metal film.